


## VISOR® Robotic

An eye on everything – the vision sensor for robotics applications



VISION SYSTEMS DESIGN  
**2020 Innovators Awards**

 made in Germany

# VISOR® Robotic

The expert sensor for robotics applications



## A diverse specialist

The expectations of today's robotics solutions are steadily rising in the context of Industry 4.0, paired with a simultaneous desire for greater ease-of-use. And this is precisely where the VISOR® Robotic demonstrates its outstanding ability. Available in several versions, it offers the perfect solution for a variety of automation tasks.

Designed with an integrated and standardised interface, VISOR® Robotic can be easily incorporated in existing installations and systems, and thanks to different calibration methods and flexible data structures, it is also suited to a diverse range of procedures.

## HIGHLIGHTS OF VISOR® ROBOTIC

- Compact and lightweight housing for mobile or stationary use
- Calibration methods tailored to the application
- 2D or 3D localisation in robot coordinates
- Simplified installation through 3D grip point transformation
- Less robot programming with diverse imaging positions
- Different hardware versions up to 5 megapixels

## Reliable feeding of material

Thanks to VISOR® Robotic, components that are fed in a universal tray or via a supply bin are reliably located and gripped. When loose components are supplied, the sensor not only checks their position but also inspects the free space around the gripper. The VISOR® determines both sets of information and sends them to the robot controller via one of the integrated standardised interfaces. The process is then managed based on the information received.

### The benefits for you:

- Cost advantage due to use of universal tray
- Precise feeding, without mechanical alignment
- Easy installation of vision sensor through slimline design and functions tailored to the application.

## Precise processing of components

With robot-guided applications, such as the placing of screws, the VISOR® Robotic detects the position of components effortlessly; this allows the correction of any offset and increases the quality of production. Mechanical effort is reduced, and the production line is consequently more flexible. The VISOR® Robotic concept enables direct communication between the VISOR® and the robot, and an additional instance can subsequently be omitted for many applications.

### The benefits for you:

- Stable process despite varying positions of parts being fed
- Added flexibility with increasing number/diversity of variants
- Reduced programming due to calculation of 3D destination position for robot by VISOR® Robotic.

## Precision for mobile workstations

Use of mobile robots must be safe and efficient. To achieve this, the size of the safety zone must be rigorously defined, and also extremely reduced to offer the worker maximum freedom of movement. The VISOR® Robotic allows mobile robots to move with precision to the workstation and e.g. to connect themselves there mechanically via a plug.

### The benefits for you:

- High availability due to robots' implementation of workstation safety zones
- Fast procedures due to compensation of 3D offset using 2D vision sensor with image capture



*The position of components supplied in a tray can vary so strongly that robot guidance is necessary.*



*The VISOR® Robotic identifies the exact position of the sensor housing. Offset data is used to correct the robot's trajectory.*



*When using mobile workstations, the key is to achieve the ideal ratio between maximum security and the greatest possible freedom of movement for the worker.*

Email your questions to the following address: [robotic@sensopart.com](mailto:robotic@sensopart.com)

VISOR® Robotic – Product overview					
Order reference	Functions	Resolution	Field of view	Alternative LED lighting	Article no.
V20-RO-A3-R-W-M2-L	Robotic	1440 x 1080 pixels	wide	white, infrared	632-91067
V20-RO-A3-R-M-M2-L			medium	white, infrared	632-91068
V20-RO-A3-R-N-M2-L			narrow	white, infrared	632-91069
V20-RO-A3-C-2			dependent on lens selected*	none	632-91073
V50-RO-P3-C-2	Robotic, identification, extended calibration, 3D localisation	2560 x 1936 pixels	dependent on lens selected*	none	635-91040
V20-RO-P3-C-2		1440 x 1080 pixels	dependent on lens selected*	none	632-91129
V20-RO-P3-R-W-M2-L			wide	white, infrared	535-91123
V20-RO-P3-R-M-M2-L			medium	white, infrared	632-91124
V20-RO-P3-R-N-M2-L			narrow	white, infrared	632-91125
V10-RO-A3-R-W-M2-L	Robotic	800 x 600 pixels	wide	white, infrared	631-91076
V10-RO-A3-R-M-M2-L			medium	white, infrared	631-91077
V10-RO-A3-R-N-M2-L			narrow	white, infrared	631-91078
V10-RO-A3-C-2			dependent on lens selected*	none	631-91082
V50C-RO-P3-C-2	Robotic, identification, extended calibration, 3D localisation, color evaluation	2560 x 1936 pixels	dependent on lens selected*	none	635-91043
V20C-RO-P3-C-2		1440 x 1080 pixels	dependent on lens selected*	none	632-91133
V20C-RO-P3-W-W-M2-L			wide	none	632-91113
V20C-RO-P3-W-M-M2-L			medium	none	632-91131
V20C-RO-P3-W-N-M2-L			narrow	none	632-91132

\* Available separately.

#### Germany

SensoPart  
Industriesensorik GmbH  
Nägelseestraße 16  
79288 Gottenheim  
Tel. +49 7665 94769-0  
[info@sensopart.de](mailto:info@sensopart.de)

#### France

SensoPart France Sarl  
662, rue des Jonchères – Bât. A  
F-69730 GENAY  
Tel. : +33 164 730061  
[info@sensopart.fr](mailto:info@sensopart.fr)

#### Great Britain

SensoPart UK Limited  
Pera Business Park, Nottingham Road  
Melton Mowbray, Leicestershire  
LE13 0PB  
Tel. +44 1664 561539  
[uk@sensopart.com](mailto:uk@sensopart.com)

#### USA

SensoPart Inc.  
30600 Telegraph Rd.  
Suite 2345,  
Bingham Farms, MI, 48025  
Tel. +1 866 2827610  
[usa@sensopart.com](mailto:usa@sensopart.com)

#### China

SensoPart China  
202, No. 35, Lane 1555  
West Jinshajiang Road, Jiading District  
201803 Shanghai  
Tel. +86 21 69017660  
[china@sensopart.cn](mailto:china@sensopart.cn)